

## SPECIFICATIONS

| Capacity<br>(tonne)                                                                               | Model   | Travel Speed<br>(ft/min) | Min. Radius for<br>Curve<br>(mm) | Trolley Motor<br>H.P. | Standard Flange (mm) |                  |                  | Standard Flange (in) |                  |                  | Ship<br>Weight<br>(lbs) |
|---------------------------------------------------------------------------------------------------|---------|--------------------------|----------------------------------|-----------------------|----------------------|------------------|------------------|----------------------|------------------|------------------|-------------------------|
|                                                                                                   |         |                          |                                  |                       | Standard             | W20<br>Extension | W30<br>Extension | Standard             | W20<br>Extension | W30<br>Extension |                         |
| Single Speed Trolley for connection to Single Speed Hoist - Three Phase (220/440/575V)            |         |                          |                                  |                       |                      |                  |                  |                      |                  |                  |                         |
| 1                                                                                                 | MR2010L | 40                       | 800                              | 0.54                  | 58 - 127             | 128 - 203        | 204 - 305        | 2.25 - 5"            | 5 - 8"           | 8 - 12"          | 66                      |
| 1                                                                                                 | MR2010S | 80                       | 800                              | 0.54                  | 58 - 127             | 128 - 203        | 204 - 305        | 2.25 - 5"            | 5 - 8"           | 8 - 12"          | 66                      |
| 2                                                                                                 | MR2020L | 40                       | 800                              | 0.54                  | 82 - 153             | ----             | 154 - 305        | 3.25 - 6"            | ----             | 6 - 12"          | 84                      |
| 2                                                                                                 | MR2020S | 80                       | 800                              | 0.54                  | 82 - 153             | ----             | 154 - 305        | 3.25 - 6"            | ----             | 6 - 12"          | 84                      |
| 3                                                                                                 | MR2030L | 40                       | 1000                             | 0.54                  | 82 - 153             | ----             | 154 - 305        | 3.25 - 6"            | ----             | 6 - 12"          | 106                     |
| 3                                                                                                 | MR2030S | 80                       | 1000                             | 0.54                  | 82 - 153             | ----             | 154 - 305        | 3.25 - 6"            | ----             | 6 - 12"          | 106                     |
| 5                                                                                                 | MR2050L | 40                       | 1800                             | 1.0                   | 100 - 178            | ----             | 179 - 305        | 4-7"                 | ----             | 7 - 12"          | 154                     |
| 5                                                                                                 | MR2050S | 80                       | 1800                             | 1.0                   | 100 - 178            | ----             | 179 - 305        | 4-7"                 | ----             | 7 - 12"          | 154                     |
| 10                                                                                                | MR2100L | 40                       | 2500                             | 1.0                   | 178 - 221            | ----             | 140 - 221        | 5.5 - 8.7"           | ----             | 8.7 - 12"        | 216                     |
| 20                                                                                                | MR2200L | 40                       | ----                             | 1.0 x 3               | 178 - 221            | ----             | 140 - 221        | 5.5 - 8.7"           | ----             | 8.7 - 12"        | 433                     |
| Single-Speed Trolley for connection to Adj. 2 Speed/Dual Speed Hoist - Three Phase (220/440/575V) |         |                          |                                  |                       |                      |                  |                  |                      |                  |                  |                         |
| 1                                                                                                 | MR2010L | 40                       | 800                              | 0.54                  | 58 - 127             | 128 - 203        | 204 - 305        | 2.25 - 5"            | 5 - 8"           | 8 - 12"          | 66                      |
| 1                                                                                                 | MR2010S | 80                       | 800                              | 0.54                  | 58 - 127             | 128 - 203        | 204 - 305        | 2.25 - 5"            | 5 - 8"           | 8 - 12"          | 66                      |
| 2                                                                                                 | MR2020L | 40                       | 800                              | 0.54                  | 82 - 153             | ----             | 154 - 305        | 3.25 - 6"            | ----             | 6 - 12"          | 84                      |
| 2                                                                                                 | MR2020S | 80                       | 800                              | 0.54                  | 82 - 153             | ----             | 154 - 305        | 3.25 - 6"            | ----             | 6 - 12"          | 84                      |
| 3                                                                                                 | MR2030L | 40                       | 1000                             | 0.54                  | 82 - 153             | ----             | 154 - 305        | 3.25 - 6"            | ----             | 6 - 12"          | 106                     |
| 3                                                                                                 | MR2030S | 80                       | 1000                             | 0.54                  | 82 - 153             | ----             | 154 - 305        | 3.25 - 6"            | ----             | 6 - 12"          | 106                     |
| 5                                                                                                 | MR2050L | 40                       | 1800                             | 1.0                   | 100 - 178            | ----             | 179 - 305        | 4 - 7"               | ----             | 7 - 12"          | 154                     |