

Description

Model: TQ700E | ECCN: EAR99 | Harmonization: 8413500070

Series: TQ | Product Line: Bolting Tools

- Optimized flow technology three stage pump maximizes productivity of the pump and tool while minimizing heat build-up and downtime
- Heat exchanger is standard
- A quiet (< 85 dBA), lightweight pump with a compact footprint â€” easy to move around
- Durable roll cage with an ergonomically sized handle and shielded gauge
- Maintenance made simple with a brushless motor designed for continuous usage
- Straightforward operation with a simple pressure set and convenient to use 20 ft. pendant cord
- IP55 Rating for superior dust and water protection
- Transparent gauge overlays in Ft.lbs and Nm for all Enerpac torque wrenches provide a quick torque reference

Series Comparison

Units: Imperial Metric

Product	Availability	Maximum Operating Pressure (bar)	For Use With Torque Wrenches	Reservoir Capacity (cm ³)	Usable Oil Capacity (litres)	Maximum Flow at Rated Pressure	Motor Hertz	Motor Phases	Motor Voltage	Valve Operation	Valve Type	Power Source	Motor Electrical Specification	Sound Level (dBa)	Weight (kg)
TQ700B	Out of stock	700	For use with all Enerpac torque wrenches	4000	4,0	0,5 l/min	50/60 Hz	1 Ph	115 V	Solenoid	4-way, 2-position	Electric	115 V, 1 Ph, 50/60 Hz	82 - 85	31
TQ700E	Out of stock	700	For use with all Enerpac torque wrenches	4000	4,0	0,5 l/min	50 Hz	1 Ph	208-240 V	Solenoid	4-way, 2-position	Electric	230 V, 1 Ph, 50 Hz	82 - 85	30
TQ700I	Out of stock	700	For use with all Enerpac torque wrenches	4000	4,0	0,5 l/min	60 Hz	1 Ph	208-240 V	Solenoid	4-way, 2-position	Electric	230 V, 1 Ph, 60 Hz	82 - 85	30